



1948 siaflex

flexible and versatile



flexible and versatile

As an all-round series for wet and dry sanding, 1948 siaflex produces outstanding results in all available grits and in a variety of automotive applications.

- ▶ High performance for stock removal with good finish
- ▶ Highly flexible and adaptable to contours
- ▶ Minimal clogging thanks to open coating in 220 - 600 grit range
- ▶ Long lifetime
- ▶ Suitable for general use in dry and wet sanding applications
- ▶ A versatile all-round product

Product profile

Grit type:	Blue-fired/white aluminium oxide	
Grit range:	40; 60-1500	
Backing:	Latex paper	
Coating:	Electrostatic	P040 – P180
	Electrostatic open	P220 – P600
	Electrostatic	P800
bonding:	Resin over resin	
Special coating:	Stearate	P180 – P800

Use



Applications

- Sanding off coatings and impurities
- Flatting bodyfiller and primer filler
- Fine sanding primer filler
- Keying of primers
- Keying old and new lacquers
- Removing orange peel effect and dust inclusions

Materials

Colour; Primer filler; Putty; Paints; Old lacquer; Primer coat; Epoxy primer coat; Plastics; Acrylic glas; Gelcoat polyester; Glass-fibre reinforced plastic (GRP); Composite; Aluminium

Technology

Open coating; S Performance; siafast; siasoft